

SURFACE MOUNT
SCHOTTKY BARRIER DIODE
VOLTAGE 30 Volts CURRENT 1.0 Ampere

CH511H-30PT

APPLICATION

* Low power rectification

FEATURE

* Small surface mounting type. (SC-76/SOD-323)
* Ultra low VF. (VF=0.47V Typ. at 1.0A)
* High reliability

CONSTRUCTION

* Silicon epitaxial planar



MARKING

* L

CIRCUIT



SC-76/SOD-323



Dimensions in millimeters

SC-76/SOD-323

MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	CH511H-30PT	UNITS
Maximum Recurrent Peak Reverse Voltage	VRRM	30	Volts
Maximum RMS Voltage	VRMS	21	Volts
Maximum DC Blocking Voltage	VDC	20	Volts
Maximum Average Forward Rectified Current	IO	1.0	Amps
Peak Forward Surge Current at 8.3 mSec single half sine-wave	IFSM	2.0	Amps
Typical Junction Capacitance between Terminal (Note 1)	CJ	15	pF
Maximum Operating Temperature Range	TJ	+125	°C
Storage Temperature Range	TSTG	-40 to +125	°C

ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	CH511H-30PT	UNITS
Maximum Instantaneous Forward Voltage at IF(1)= 100mA	VF(1)	0.36	Volts
Maximum Instantaneous Forward Voltage at IF(2)= 1000mA	VF(2)	0.47	Volts
Maximum Average Reverse Current at VR= 20V	IR	100	uAmps

NOTES : 1. Measured at 1.0 MHz and applied reverse voltage of 10.0 volts.
2. ESD sensitive product handling required.

RATING CHARACTERISTIC CURVES (CH511H-30PT)

FIG. 1 - FORWARD CHARACTERISTICS




FIG. 2 - REVERSE CHARACTERISTICS




FIG. 3 - TYPICAL JUNCTION CAPACITANCE




FIG. 4 - TYPICAL FORWARD CURRENT DERATING CURVE

