


ESD Safe – High Voltage Power Schottky – Rectifier

Features

- High efficiency
- Low forward voltage drop
- Negligible switching losses
- Low reverse current
- High reverse surge capability
- High ESD capability



15 811

Applications

High frequency SMPS

Free wheeling diode in low voltage converters

Absolute Maximum Ratings

 $T_j = 25^{\circ}\text{C}$

Parameter	Test Conditions	Type	Symbol	Value	Unit
Repetitive peak reverse voltage			V_{RRM}	90	V
Continuous reverse voltage			V_R	90	V
Average forward current	$T_j = 76^{\circ}\text{C}$, $V_R = 90\text{V}$		I_{FAV}	1.5	A
Non-repetitive surge forward current	$t_p = 10\text{ms}$, half sinewave		I_{FSM}	75	A
ESD – IEC 1000–4–2	$R = 330\Omega$, $C = 150\text{pF}$		ESD	20	kV
Junction and storage temperature range			$T_j = T_{stg}$	$-55...+150$	$^{\circ}\text{C}$

Maximum Thermal Resistance

 $T_j = 25^{\circ}\text{C}$

Parameter	Test Conditions	Symbol	Value	Unit
Junction lead	$T_L = \text{constant}$	R_{thJL}	25	K/W
Junction ambient	Epoxy–glass hard tissue (see figure 1) $35\mu\text{m} \times 17\text{mm}^2$ copper area per electrode	R_{thJA}	150	K/W
	Epoxy–glass hard tissue (see figure 2) $35\mu\text{m} \times 50\text{mm}^2$ copper area per electrode		125	

Electrical Characteristics

 $T_j = 25^{\circ}\text{C}$

Parameter	Test Conditions	Type	Symbol	Min	Typ	Max	Unit
Forward voltage	$I_F = 100\text{mA}$		V_F			430	mV
	$I_F = 3\text{A}$				850	950	
	$I_F = 3\text{A}$, $T_j = 100^{\circ}\text{C}$				700	850	
Reverse current	$V_R = V_{RRM}$		I_R			30	μA
	$V_R = V_{RRM}$, $T_j = 100^{\circ}\text{C}$					5	mA
Junction Capacitance	$V_R = 4\text{V}$, $f = 1\text{MHz}$		C_D		130		pF


Characteristics ($T_j = 25^\circ\text{C}$ unless otherwise specified)

Figure 1. Forward Current vs. Forward Voltage




Figure 4. Reverse Current vs. Junction Temperature




Figure 2. Max. Average Forward Current vs. Ambient Temperature




Figure 5. Max. Reverse Power Dissipation vs. Junction Temperature




Figure 3. Max. Average Forward Current vs. Ambient Temperature







Figure 6. Diode Capacitance vs. Reverse Voltage

Dimensions in mm



Plastic case JEDEC DO 214
similar to SMA
Cathode indicated by a band



technical drawings
according to DIN
specifications

14275

Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay-Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay-Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0) 7131 67 2831, Fax number: 49 (0) 7131 67 2423