

isc Silicon NPN Power Transistors

BDT29F/AF/BF/CF/DF

DESCRIPTION

- DC Current Gain $-h_{FE} = 40(\text{Min})@ I_C = 0.4\text{A}$
- Collector-Emitter Sustaining Voltage-
: $V_{CEO(\text{SUS})} = 40\text{V}(\text{Min})$ - BDT29F; $60\text{V}(\text{Min})$ - BDT29AF
80V(Min)- BDT29BF; $100\text{V}(\text{Min})$ - BDT29CF
120V(Min)- BDT29DF
- Complement to Type BDT30F/AF/BF/CF/DF

APPLICATIONS



- Designed for use in audio output stages , general purpose amplifier and high speed switching applications

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER		VALUE	UNIT
V_{CBO}	Collector-Base Voltage	BDT29F	80	V
		BDT29AF	100	
		BDT29BF	120	
		BDT29CF	140	
		BDT29DF	160	
V_{CEO}	Collector-Emitter Voltage	BDT29F	40	V
		BDT29AF	60	
		BDT29BF	80	
		BDT29CF	100	
		BDT29DF	120	
V_{EBO}	Emitter-Base Voltage		5	V
I_C	Collector Current-Continuous		1	A
I_{CM}	Collector Current-Peak		3	A
I_B	Base Current		0.4	A
P_C	Collector Power Dissipation $T_C=25^{\circ}\text{C}$		19	W
T_j	Junction Temperature		150	$^{\circ}\text{C}$
T_{stg}	Storage Ttemperature Range		-65~150	$^{\circ}\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance,Junction to Case	9.17	$^{\circ}\text{C/W}$
$R_{th\ j-a}$	Thermal Resistance,Junction to Ambient	55	$^{\circ}\text{C/W}$



isc Silicon NPN Power Transistors

BDT29F/AF/BF/CF/DF

ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage	BDT29F	$I_C=30\text{mA}; I_B=0$	40			V
		BDT29AF		60			
		BDT29BF		80			
		BDT29CF		100			
		BDT29DF		120			
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage		$I_C=1\text{A}; I_B=0.125\text{A}$			0.7	V
$V_{BE(on)}$	Base-Emitter On Voltage		$I_C=1\text{A}; V_{CE}=4\text{V}$			1.3	V
I_{CES}	Collector Cutoff Current		$V_{CE}=V_{CEOmax}; V_{BE}=0$			0.2	mA
I_{CEO}	Collector Cutoff Current	BDT29F/AF	$V_{CE}=30\text{V}; I_B=0$			0.1	mA
		BDT29BF/CF	$V_{CE}=60\text{V}; I_B=0$				
		BDT29DF	$V_{CE}=90\text{V}; I_B=0$				
I_{EBO}	Emitter Cutoff Current		$V_{EB}=5\text{V}; I_C=0$			0.2	mA
h_{FE-1}	DC Current Gain		$I_C=0.2\text{A}; V_{CE}=4\text{V}$	40			
h_{FE-2}	DC Current Gain		$I_C=1\text{A}; V_{CE}=4\text{V}$	15		75	
f_T	Current-Gain—Bandwidth Product		$I_C=0.2\text{A}; V_{CE}=10\text{V}$	3			MHz

Switching Times

t_{on}	Turn-On Time	$I_C=1.0\text{A}; I_{B1}=-I_{B2}=0.1\text{A}$		0.3		μs
t_{off}	Turn-Off Time			1.0		μs