

**SOT-323 SURFACE MOUNT SCHOTTKY  
BARRIER DIODE**

**FEATURES**

- \* Low forward voltage drop
  - \* Fast switching
  - \* Ultra - small surface mount package
  - \* PN Junction guard ring for transient and ESD protection
- Marking: KL5

**MECHANICAL DATA**


- \* Case: Molded plastic
- \* Epoxy: UL 94V-O rate flame retardant
- \* Lead: MIL-STD-202E method 208C guaranteed
- \* Mounting position: Any
- \* Weight: 0.006 gram

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25 °C ambient temperature unless otherwise specified.



**SOT-323**



**MAXIMUM RATINGS** ( @ TA = 25°C unless otherwise noted )

CHARACTERISTICS	SYMBOL	VALUE	UNITS
Peak repetitive reverse voltage	VRRM	30	V
working peak reverse voltage	VRWM	30	
DC blocking voltage	VR	30	
Forward continuous current (Note 1)	IF	200	μA
Repetitive peak forward current (Note 1)	IFRM	300	μA
Forward surge current (Note 1) @ t < 1.0 s	IFSM	600	μA
Power dissipation (Note 1)	PD	200	μW
Thermal resistance, Junction to ambient air (Note 1)	R JA	625	K/Ω
Operating and storage temperature range	Tj, Tstg	-65~+125	°C

**ELECTRICAL CHARACTERISTICS** ( @ TA = 25°C unless otherwise noted )

CHARACTERISTICS	SYMBOL	MIN	TYP	MAX	UNITS
Reveres breakdown voltage (IRS= 100μA)	V(BR)R	30	-	-	V
Forward voltage (Note 2)	VF	(IF= 0.1mA)	-	240	mV
		(IF= 1mA)	-	320	
		(IF= 10mA)	-	400	
		(IF= 30mA)	-	500	
		(IF= 100mA)	-	1000	
Reverse leakage current (VR= 25V) (Note 2)	IR	-	-	2.0	μA
Junction capacitance (VR= 1.0V, f= 1.0MHz)	Cj	-	-	10	pF
Reveres recovery time (IF=10mA through IR=10mA to IR=1.0mA,RL=100 )	trr	-	-	5.0	ns

**Notes:** 1. Valid provided that terminals are kept at ambient temperature.  
2. tp <300μs, duty cycle <2%.

2006-3

## DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.