



Low VF Schottky Diode

- Forward current: 1 A
- Reverse voltage: 30 V
- Low forward voltage and smallest package form factor (1.0 x 0.6 x < 0.4 mm) for mobile phone battery charger application
- Pb-free (RoHS compliant) package¹⁾
- Qualified according AEC Q101



BAS3010S-03LRH



Type	Package	Configuration	Marking
BAS3010S-03LRH*	TSLP-3-7	single	1S

* Preliminary data

Maximum Ratings at $T_A = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Value	Unit
Diode reverse voltage ²⁾	V_R	30	V
Forward current ²⁾³⁾	I_F	1	A
Repetitive peak forward current ³⁾ ($t_p \leq 1 \text{ ms}$, $D \leq 0.25$)	I_{FPM}	3.5	
Non-repetitive peak surge forward current ³⁾ ($t \leq 10 \text{ ms}$)	I_{FSM}	5	
Junction temperature	T_j	150	$^\circ\text{C}$
Operating temperature range	T_{op}	-55 ... 125	
Storage temperature	T_{stg}	-65 ... 150	

¹Pb-containing package may be available upon special request

²For $T_A > 25^\circ\text{C}$ the derating of V_R and I_F has to be considered.

³Only valid if pin 1 and 2 are connected in parallel

Thermal Resistance

Parameter	Symbol	Value	Unit
Junction - soldering point ¹⁾	R_{thJS}	≤ 38	K/W

Electrical Characteristics at $T_A = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	

DC Characteristics

Reverse current ²⁾ $V_R = 5 \text{ V}$ $V_R = 10 \text{ V}$ $V_R = 30 \text{ V}$	I_R	-	-	-	μA
		-	-	15	
		-	-	30	
		-	-	300	
Forward voltage ²⁾ $I_F = 100 \text{ mA}$ $I_F = 350 \text{ mA}$ $I_F = 1000 \text{ mA}$	V_F	-	-	-	mV
		-	340	390	
		-	400	450	
		-	570	650	

AC Characteristics


Diode capacitance $V_R = 5 \text{ V}, f = 1 \text{ MHz}$	C_T	-	10	15	pF
---	-------	---	----	----	-------------

¹For calculation of R_{thJA} please refer to Application Note Thermal Resistance

²Pulsed test: $t_p = 300 \mu\text{s}$; D = 0.01


Diode capacitance $C_T = f (V_R)$

$f = 1\text{MHz}$




Reverse current $I_R = f(V_R)$

T_A = Parameter




Reverse current $I_R = f(T_A)$

V_R = Parameter




Forward Voltage $V_F = f(T_A)$

I_F = Parameter




Forward current $I_F = f(V_F)$

T_A = Parameter




Package Outline



Foot Print

For board assembly information please refer to Infineon website "Packages"




Marking Layout



Standard Packing

Reel ø180 mm = 15.000 Pieces/Reel



Edition 2006-02-01

Published by

Infineon Technologies AG

81726 München, Germany

© Infineon Technologies AG 2007.

All Rights Reserved.

Attention please!

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system.

Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.