

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0014567026

Status:

Active

Overview:

cgrid_sl_products

Description:

2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22, 0.38µm (15µ") Gold (Au), 2 Circuits

Documents:

3D Model

Drawing (PDF)

Product Specification PS-70400 (PDF)


RoHS Certificate of Compliance (PDF)

Agency Certification	
CSA	LR19980
UL	E29179
General	
Product Family	Ribbon Cable / Wire Trap Connectors
Series	70400
Comments	Terminals Preloaded
Component Type	Housing
Glow-Wire Compliant	No
Overview	cgrid_sl_products
Product Name	SL™

Physical	
Circuits (Loaded)	2
Color - Resin	Black
Durability (mating cycles max)	50
Entry Angle	Vertical
Flammability	94V-0
Lock to Mating Part	None
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Polyester Alloy
Number of Rows	1
PCB Retention	None
Packaging Type	Tube
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Plating min: Mating (µin)	15
Plating min: Mating (µm)	0.375
Plating min: Termination (µin)	75
Plating min: Termination (µm)	1.875
Polarized to Mating Part	Yes
Stackable	Yes
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	IDT or Pierce
Wire Insulation Diameter	1.35mm (.053") max.
Wire Size AWG	22
Wire/Cable Type	Discrete Wire, Ribbon Cable

Electrical	
Current - Maximum per Contact	3A
Voltage - Maximum	250V

Material Info



EU RoHS

ELV and RoHS Compliant

REACH SVHC Not Reviewed

Halogen-Free Status Not Reviewed

Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

China RoHS



Search Parts in this Series

70400Series

Mates With

70004 Interim Clip (Single Row), 70013 Interim Clip (Dual Row)

Use With

7307 Tinned 28AWG, 7767 Topcoat 28AWG, 24241 Tinned 26AWG, 8996 Topcoat 26AWG, 24226 Tinned 24AWG, 8997 Topcoat 24AWG, 24369 High Flex 26AWG, 24389 High Flex 24AWG

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Hawk Semi-Automatice Discrete	0011201337

Old Part Number	70400-3245	Wire Terminator for SL - Rebuilt US*
Reference - Drawing Numbers		Hawk™ Ribbon <u>0623003000</u>
Product Specification	PS-70400	Cable Terminator for SL without Break-off
Sales Drawing	SDA-70400-3245-3268	Hawk™ Semi- <u>0623004900</u> Automatic Discrete
		Wire Terminator for SL - Rebuilt CE
		Approved*
		Hawk™ Flat Flex <u>0623005200</u>
		Cable Terminator for SL with Break-off
		Hawk™ Ribbon <u>0623005300</u>
		Cable Terminator with for SL Break-off
		IDT Discrete <u>0621000700</u>
		Handtool Module for SL™
		Hawk™ Semi- <u>0623003100</u> Automatic Discrete
		Wire Terminator for SL

This document was generated on 05/21/2010
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

OPTION D


NOTES:

- 1) TO BE USED WITH (22) AWG. STRANDED WIRE WITH (1.35)/.053 DIA. MAX. INSULATION.
- 2) SEE CHART FOR CIRCUIT SIZES.
- 3) STANDARD PACKAGING PER PK-70400-0001. OPTIONAL PACKAGING MAY BE AVAILABLE, REQUEST DWG. PK-70400
- 4) PARTS STACKABLE END TO END ON (2.54)/.100 CENTERS.
- 5) REFER TO PRODUCT SPECIFICATION: PS-70400.
- 6) SEE DWG. SDA-70400-**** (SHT. 5) FOR OPTIONAL HOUSING DETAILS.
- 7) 4 CIRCUIT SHOWN. 3 - 25 CKT'S. HAVE (2) RIBS.
- 8) TO MATE WITH MOLEX PART NO'S.: 70004-****, 70013-****


9) 2 CIRCUIT ASSEMBLIES SUPPLIED AS GROUPED PAIRS.



SECTION C-C




PRE-LOADED ASSEMBLY




FINAL ASSEMBLY

CIRCUIT NO. 1
SLOT OR ARROW



SEE NOTE (7)



HOUSING PART NO. 70066-****
MATERIAL: G.F. POLYESTER, 94V-0

TERMINAL PART NO. 70028-****
MATERIAL: PHOSPHOR BRONZE
PLATING PER ES-88-***

15 GOLD - .000015 MIN. GOLD IN SELECT AREA WITH .000075 MIN. TIN
IN SELECT AREA OVER .000050 MIN. NICKEL OVER-ALL.

*THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH LEAD.

I.D. SLOT CODE TO WIRE GAUGE CHART	
I.D. SLOT CODE	WIRE GAUGE
D	22 AWG.

PLATING CODE (STRIPE ON CARRIER STRIP)	
PLATING	COLOR
15 GOLD	YELLOW

CKT. SIZE	A	B	EDP. NO.	ENG. NO.
2	(2.54) .100	(5.05) .199	14-56-7026	A-70400-3245
3	(5.08) .200	(7.59) .299	14-56-7036	A-70400-3246
4	(7.62) .300	(10.13) .399	14-56-7046	A-70400-3247
5	(10.16) .400	(12.67) .499	14-56-7056	A-70400-3248
6	(12.70) .500	(15.21) .599	14-56-7066	A-70400-3249
7	(15.24) .600	(17.75) .699	14-56-7076	A-70400-3250
8	(17.78) .700	(20.29) .799	14-56-7086	A-70400-3251
9	(20.32) .800	(22.83) .899	14-56-7096	A-70400-3252
10	(22.86) .900	(25.37) .999	14-56-7106	A-70400-3253
11	(25.54) 1.000	(27.91) 1.099	14-56-7116	A-70400-3254
12	(27.94) 1.100	(30.45) 1.199	14-56-7126	A-70400-3255
13	(30.48) 1.200	(32.99) 1.299	14-56-7136	A-70400-3256
14	(33.02) 1.300	(35.53) 1.399	14-56-7146	A-70400-3257
15	(35.56) 1.400	(38.07) 1.499	14-56-7156	A-70400-3258
16	(38.01) 1.500	(40.61) 1.599	14-56-7166	A-70400-3259
17	(40.64) 1.600	(43.15) 1.699	14-56-7176	A-70400-3260
18	(43.18) 1.700	(45.69) 1.799	14-56-7186	A-70400-3261
19	(45.72) 1.800	(48.23) 1.899	14-56-7196	A-70400-3262
20	(48.26) 1.900	(50.77) 1.999	14-56-7206	A-70400-3263
21	(50.80) 2.000	(53.31) 2.099	14-56-7216	A-70400-3264
22	(53.34) 2.100	(55.85) 2.199	14-56-7226	A-70400-3265
23	(55.88) 2.200	(58.39) 2.299	14-56-7236	A-70400-3266
24	(58.42) 2.300	(60.93) 2.399	14-56-7246	A-70400-3267
25	(60.96) 2.400	(63.47) 2.499	14-56-7256	A-70400-3268

DIMENSIONS SHOWN (METRIC) INCH			UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°	
			INCH	METRIC
3 PLACE	± .010	---	---	---
2 PLACE	± .014	± 0.25	---	---
1 PLACE	---	± 0.35	---	---
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			DRAWG. BY: AAB CHK'D. BY: WAZ	
APPR. BY:			SCALE: 4:1	
LTR.	REVISIONS	LTR.	REVISIONS	
D	LEAD FREE UCP2004-1769 RWHITE 04/03/22	B	REVISE PER ECR #U80110 2/3/88 MJM	
CI	ADD CARRIER CHAMF ECN #UDT1998-0280 05/20/98 LMCGRATH	A	RELEASE FOR PROD. PER ERO NO. 25421 10-26-87 AAB	
REVISED PER ECR NO. U82110 10-17-88 AAB			TITLE: ASSEMBLY, SL CONNECTOR (SINGLE ROW- (2.54)/.100 GRID)	
PART NO. 74003245			MOLEX INCORPORATED	
LITSE,ILL. 60532			SHEET NO. 10/26/87	
FILE NAME: 74003245.DGN			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	
			DIV. DA	