






Notes: Unless Otherwise Specified:

- 1.0 Connector Electrical Characteristics:
- 1.1 Withstanding Voltage: DC 500+50V
- 1.2 Insulation Resistance: 100 megohms min.
- 1.3 Contact Resistance: 30 milliohms max
- 2.0 Materials:
- 2.1 Housing: High Temperature Thermoplastics UL94V-0
- 2.2 Shell: Copper Alloy
- 2.3 Contacts: Copper Alloy
- 2.3 Back Shell: Steel
- 3.0 Finish:
- 3.1 Shell: Tin-Lead or Bright Tin-Lead Plating
- 3.2 Contacts: Plated Gold in Mating Area: Tin-Lead on Tails
- 4.0 Others:
- 4.1 All Dimensions are in millimeters with Inch Equivalents Shown in Brackets
- 4.2 Dimensioning Per ANSI Y14.5m-1982
- 4.3 The Drawing are Redrew.

RoHS
Compliant

ITEM NO

A-IE-S-SMT-R

TITLE

IEEE 1394, for PCB Mounting, SMD Version

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283

Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED

© Copyright 2008 by Assmann Electronic Components
All International Rights Reserved