

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0908140010](#)
Status: **Active**
Overview: [picoflex](#)
Description: 1.27mm (.050") Pitch Picoflex® PF-50 Header, Vertical, Low Profile, Surface Mount, 10 Circuits, Glow Wire Compatible

Documents:
[3D Model](#) [Product Specification PS-99020-0011 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification


UL E29179

General

Product Family PCB Headers
Series [90814](#)
Application Wire-to-Board
Application Tooling Part Link 690081070
Comments Low Profile SMT
Overview [picoflex](#)
Product Name Picoflex®

Physical

Breakaway No
Circuits (Loaded) 10
Color - Resin Natural
Durability (mating cycles max) 30
First Mate / Last Break No
Flammability 94V-0
Glow-Wire Compliant Yes
Guide to Mating Part No
Keying to Mating Part None
Lock to Mating Part Yes
Material - Metal Brass
Material - Plating Mating Tin
Material - Resin High Temperature Thermoplastic
Number of Rows 1
Orientation Vertical
PCB Locator Yes
PCB Retention Yes
PCB Thickness Recommended (in) 0.062 In
PCB Thickness Recommended (mm) 1.60 mm
Packaging Type Tube
Pitch - Mating Interface (in) 0.050 In
Pitch - Mating Interface (mm) 1.27 mm
Plating min: Mating (µin) 120
Plating min: Mating (µm) 3
Plating min: Termination (µin) 120
Plating min: Termination (µm) 3
Polarized to Mating Part Yes
Polarized to PCB Yes
Shrouded No
Stackable No
Surface Mount Compatible (SMC) N/A
Temperature Range - Operating -40°C to +105°C
Termination Interface: Style Surface Mount



Series

image - Reference only

EU RoHS

**ELV and RoHS
Compliant**

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[90814Series](#)

Mates With

[90327 IDT Connector](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Extraction Tool (Plastic) for 90327 Connector, 4-26 Circuit	0690081070

Electrical

Current - Maximum per Contact	1.2A
Voltage - Maximum	250V





Material Info

Reference - Drawing Numbers


Packaging Specification	PK-90814-001
Product Specification	PS-99020-0011
Sales Drawing	SDA-90814

This document was generated on 05/26/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



SECTION Y-Y



(SCALE 10:1)

NOTES:

- MATERIAL: HOUSING: NYLON 4/6 30% G.F., UL 94 V-0, NATURAL (BEIGE)
TERMINAL- CARTRIDGE BRASS (0.28)/.011 REF THICK
- PLATING:
TIN: TIN (3-5UM)/120UM-200UM OVER (1.27UM)/5UM MIN NICKEL.
GOLD: (0.76UM)/30UM SELECTIVE GOLD AND
(0.10-0.20UM)/4UM-8UM GOLD FLASH OVER (1.27UM)/50UM
NICKEL UNDERCOAT
- MATES WITH MOLEX 90327 PART SERIES
- ALL SMT TAILS TO LIE WITHIN A COPLANARITY BAND OF
(0.0)/.0 - (0.10)/.004 REF. FROM EACH OTHER.
- FOR TAPE & REEL PACKAGING DETAILS SEE SDA-90814-9001
- PCB PEGS ARE OPTIONAL
- PCB LAYOUT SHOWN ON SHEET 2

90814 - **

CIRCUIT SIZE

	PCB PEGS	TUBE PACKED	TAPE & REEL PACKED	POLARIZING PEG HEIGHT DIMN. E
0	YES	YES	NO	(6.40)/ .252
2	YES	NO	YES	(6.40)/ .252
3	NO	YES	NO	(6.40)/ .252
5	NO	NO	YES	(6.40)/ .252
6	NO	YES	NO	(4.10)/ .161
7	NO	NO	YES	(4.10)/ .161
8	YES	YES	NO	(4.10)/ .161
9	YES	NO	YES	(4.10)/ .161

0= (3-5UM)/120-200UM TIN VERSION

3= (0.76UM)/30UM GOLD VERSION

90814--34	34	(46.96)/.1849	(41.91)/.1650	(45.76)/.1802	10	NO
90814--26	26	(36.80)/.1449	(31.75)/.1250	(35.60)/.1402	14	YES
90814--24	24	(34.26)/.1349	(29.21)/.1150	(33.06)/.1302	15	YES
90814--22	22	(31.72)/.1249	(26.67)/.1050	(30.52)/.1202	16	YES
90814--20	20	(29.18)/.1149	(24.13)/.0950	(27.98)/.1102	18	YES
90814--18	18	(26.64)/.1049	(21.59)/.0850	(25.44)/.1002	20	YES
90814--16	16	(24.10)/.0949	(19.05)/.0750	(22.90)/.0902	22	YES
90814--14	14	(21.56)/.0849	(16.51)/.0650	(20.36)/.0802	25	YES
90814--12	12	(19.02)/.0749	(13.97)/.0550	(17.82)/.0702	28	YES
90814--10	10	(16.48)/.0649	(11.43)/.0450	(15.28)/.0602	32	YES
90814--08	8	(13.94)/.0549	(8.89)/.0350	(12.74)/.0502	38	YES
90814--06	6	(11.40)/.0449	(6.35)/.0250	(10.20)/.0402	46	YES
90814--04	4	(8.86)/.0349	(3.81)/.0150	(7.66)/.0302	60	YES
PART NO.	NUMBER OF CKTS	DIMN. A	DIMN. B	DIMN. C	QUANTITY OF PARTS PER TUBE (-0**/-3**/-6** & -8** VERSIONS)	TOOLED

REDUCED CO-PL TOL EC NO: E2007-0304 DRAWN: JENNEY 2006/11/07 CHKD: JENNEY 2006/11/07 APPR: JENNEY 2006/11/13	QUALITY SYMBOLS =0 =0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		4 PLACES ± --- ± --- 3 PLACES ± --- ± .004 2 PLACES ± 0.10 ± --- 1 PLACE ± --- ± --- ANGULAR ±1/2°	mm INCH	DRAWN BY DATE DMCNAMAR 2001/08/16 CHECKED BY DATE PCURTIN 2001/08/16 APPROVED BY DATE MWILHITE 2001/08/16	TITLE PICO FLEX SMT HEADER		MOLEX INCORPORATED		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		MATERIAL NO. DOCUMENT NO. SDA-90814		SHEET NO. 1 OF 2			

